

TECHNICAL DATA SHEET

GD103DNRVAI

Day/Night Mini Dome With 4mm Fixed Lens



KEY FEATURES

- 1/3" Sony Super CCD
- Super High Resolution
- Digital Noise Reduction
- Easy To Fit
- O.S.D.
- Privacy Masking, Mirror
- Three Axis Gimbal

OPTIONAL ACCESSORIES

CCTV Power Supply In-Line 12V DC 500mA Regulated Linear Power Supply Unit with Fixing Mount.

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	GD103DNRVAI
Image Sensor	1/3" Sony CCD
Horizontal Resolution	540 TVL
Sensitivity (F1.2)	0.3 Lux (Col) 0.1 Lux (B/W) 0.002 Lux (Sens-Up)
Lens	2.9-10mm DC AI Varifocal
Effective Pixels (H x V)	752 x 582
Electronic Shutter Speed	Auto / Manual (1/50~1/120,000 Seconds)
Scanning System	2:1 Interlace
Synchronisation	INT/LL Selectable 0~359° (Adjustable)
Frequency	Horizontal: 15.625KHz Vertical: 50.00Hz
Video Output	1.0Vp-p~75 Ohm (Video 0.7 Vp-p Sync 0.3 Vp-p)
S/N Ratio	>50dB (AGC Off)
Gain Control	OFF / LOW / MIDDLE / HIGH
White Balance	ATW / AWC / MANUAL (1800°K~10500°K)
Sens-Up	OFF / AUTO
O.S.D.	Built-In
Motion Detection	ON / OFF (4 Programmable Zones)
DNR	OFF / LOW / MIDDLE / HIGH
Mirror	Built-In (Horizontal Image Inversion)
Privacy Function	ON / OFF (4 Programmable Zones)
Operating Conditions	Temperature: -10°C ~ +50°C, Humidity: 30 ~ 90% RH
Power Supply	DC 12V
Power Consumption	160mA
Dimensions (D x H)	120 x 100mm
Weight	360g

Features and specification are subject to change for further improvement without any notice.

Authorized Distributor



P O Box 55370, Dubai, U.A.E.
 Tel: +9714 3938989
 Fax: +9714 3939912
 email: sales@bcfargo.ae
 website : www.bcfargo.ae